

ULTRA POWER STRIP LED

RL LED STRIP: ENERGY SAVING IN DECORATION

RL LED-Strips offer many installation options, they are suitable for decoration, for peripheral illumination as for example furniture and counters, or behind paintings and mirrors.

The included clips make this product very easy to install.

STRISCE A LED RL: IL RISPARMIO ENERGETICO NELLA DECORAZIONE

Le strisce a LED RL offrono numerose possibilità di installazione, sono infatti adatte per la decorazione, per l'illuminazione periferica come ad esempio mobili o banconi, o dietro a quadri e specchi.

Le clip incluse rendono questo prodotto molto facile da installare.

LED-STREIFEN RL: STROMSPAREN IM DEKORATIONSBEREICH

Die LED-Lichtstreifen RL bieten zahlreiche Montagemöglichkeiten an. Sie sind für die Dekoration, für die periphere Beleuchtung, wie zum Beispiel bei Möbel und Theken, oder hinter Bildern und Spiegeln geeignet.

Mit den beigegefügt Clips können sie leicht montiert werden.



TECHNICAL DATA

ARTICLE NUMBER	110051WUSL	110051NUSL	110051CUSL
NAME OF PRODUCT	ULTRA POWER STRIP LED		
INNER CARTON	5 m/roll	5 m/roll	5 m/roll
MASTER CARTON	70 rolls	70 rolls	70 rolls
WEIGHT SINGLE PIECE	0,2 Kg	0,2 Kg	0,2 Kg

GENERAL CHARACTERISTICS

MAIN APPLICATION	Advertising box, sidewalk and architectural lighting illumination		
NOMINAL LIFETIME	> 40.000 hours	> 40.000 hours	> 40.000 hours
SOURCE (LED TYPE)	2835 SMD LED	2835 SMD LED	2835 SMD LED
IP RATE	IP 65	IP 65	IP 65

LIGHTING DATA

COLOR TEMPERATURE	3.000 K	4.000 K	6.000 K
CRI	>85	>85	>85
LUMINOUS FLUX	24 LUMEN FOR LED	24 LUMEN FOR LED	24 LUMEN FOR LED
LLMF (LUMEN MAINTENANCE)	70% AFTER 25.000 hrs	70% AFTER 25.000 hrs	70% AFTER 25.000 hrs
RATED BEAM ANGLE	>120°	>120°	>120°

ELECTRICAL DATA

SYSTEM POWER	19,9 W/M	19,9 W/M	19,9 W/M
START TIME (SECOND)	< 1S	< 1S	< 1S
WARM-UP TIME TO 60% LIGHT OUTPUT	INSTANT FULL LIGHT	INSTANT FULL LIGHT	INSTANT FULL LIGHT
INPUT VOLTAGE	DC 12/24V	DC 12/24V	DC 12/24V
OUTPUT CURRENT	1,08A	1,08A	1,08A
POWER FACTOR	> 0,90	> 0,90	> 0,90
DIMMABLE	AVAILABLE	AVAILABLE	AVAILABLE
ENERGY SAVING	YES	YES	YES
WORKING TEMPERATURE	-20/40° C	-20/40° C	-20/40° C
HUMIDITY	NO LIMIT IS IP65	NO LIMIT IS IP65	NO LIMIT IS IP65

DIMENSION

DIMENSION OF THE PRODUCT	10x5.000 mm	10x5.000 mm	10x5.000 mm
CUTOUT	NONE	NONE	NONE

APPROVAL & APPLICATIONS CHARS

VDE MARKING	-	-	-
CE MARKING	YES	YES	YES
UL MARKING	-	-	-
ROHS COMPLIANCE	YES	YES	YES